

SECTION I

NM 2/01

Chart 18581

NM 2/01

YAUQUINA BAY AND RIVER CHANNEL DEPTHS							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO OCT 2000							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
CHANNEL ENTRANCE 44°36'23"N, 124°05'24"W TO FIRST TURN	24	30	27	10-00	400-300	1.3	40-30
THENCE TO TURNING BASIN	21	29	18	6-99; 4-00	300-400	1.3	30
TURNING BASIN	15	24	24	4-00	300-1200	0.3	30
THENCE TO YAUQUINA	13	12	12	6-00	200	1.6	18
THENCE TO END OF PROJECT	02A	07	05B	7-99; 7-00	150	9.7	10

A. SHOAL TO BARE AT 44°36'57.7"N, 123°56'34.2"W.
 B. SHOAL TO BARE AT 44°36'42.0"N, 123°56'55.5"W.
 NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

Chart 18663

NM 2/01

SAN JOAQUIN RIVER-STOCKTON DEEP WATER CHANNEL							
TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO APR 2000							
CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
LIGHT 2 (CHART 18661) TO LIGHT 6	35.6	35.7	36.0	4-00	225	1.5	35
THENCE TO LIGHT 16	33.7	34.9	31.9	4-00	225-250	2.8	35
THENCE TO LIGHT 24	31.5	34.0	29.8	4-00	225-250	2.1	35
THENCE TO LIGHT 34	32.2	33.8	31.0	2,4-00	250	1.5	35
THENCE TO LIGHT 43	33.3	34.0	31.1	2,4-00	200-250	3.4	35
THENCE TO LIGHT 48	33.1	32.5	30.3	4-00	225-250	1.1	35
THENCE TO TURNING BASIN	30.9	33.6	33.3	4-00	225-250	0.8	35
TURNING BASIN	33.1	33.5	33.3	4-00	225-975	0.3	35

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION