

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
36755	- Channel Buoy 14A	40 33 17 N 74 14 31 W				Red nun.	
		*					41/03
CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18990	LUSBY POINT JUNCTION LIGHT	38 20 04 N 76 26 50 W	<b>FI (2+1) G 6s</b>	15	3	JG on pile.	
		*					41/03
19405	- Channel Daybeacon 3					SG on pile.	
	*						41/03
19415	- CHANNEL LIGHT 7		<b>Q G</b>	15	3	SG on pile.	
	*						41/03
19420	- Channel Daybeacon 9					SG on pile.	
	*						41/03
19430	- Channel Daybeacon 10						<i>Remove from list.</i>
							* 41/03
21720	- LIGHT 9		<b>FI G 4s</b>	15	4	SG on pile.	
						*	41/03
23370	- CHANNEL LIGHT 5		<b>FI G 4s</b>	16	4	SG on pile.	
						*	41/03
23920	- CHANNEL LIGHT 45	38 20 23 N 75 40 12 W	<b>FI G 4s</b>	15	4	SG on multi-pile structure.	
						*	41/03
23980	- LIGHT 6		<b>Q R</b>	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			41/03
24465	HEARNS COVE CHANNEL LIGHT 3	38 16 23 N 76 05 36 W	<b>FI G 4s</b>	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
						*	41/03
24470	HEARNS COVE CHANNEL LIGHT 5		<b>FI G 6s</b>	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
						*	41/03
24515	MIDDLE ISLAND BRIDGE WEST CHANNEL LIGHT 1	38 17 42 N 76 12 48 W	<b>FI G 4s</b>	15	4	SG on pile.	
						*	41/03

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24545	- CHANNEL LIGHT 15		FI G 6s	15	4	SG on multi-pile structure.	
					*		41/03
24550	- CHANNEL LIGHT 17	38 21 04 N 76 13 05 W	FI G 4s	15	4	SG on pile.	
					*		41/03
24600	- CHANNEL LIGHT 5	38 20 49 N 76 14 51 W	FI G 6s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
					*		41/03
24610	- CHANNEL LIGHT 7	38 20 39 N 76 14 09 W	FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
					*		41/03
24730	- LIGHT 9		FI G 4s	15	4	SG on multi-pile structure.	
					*		41/03
25940	- EAST CHANNEL LIGHT 3	38 42 35 N 76 19 25 W	FI G 4s	15	4	SG on multi-pile structure.	
					*		41/03
26200	- LIGHT 7		FI G 4s	15	5	SG on multi-pile.	
					*		41/03
<b>Cox Creek</b>							
26265	- LIGHT 2CC	38 53 56 N 76 18 51 W	FI R 2.5s	15	4	TR on pile.	Higher intensity beam down the channel. Light equipment removed from Dec. 1 to Mar. 15.
					*		41/03
<b>CHESTER RIVER (Chart 12272)</b>							
<b>Kent Island Narrows</b>							
26345	- LIGHT 1K	38 57 14 N 76 14 36 W	FI G 4s	18	4	SG on pile.	Higher intensity down channel.
					*		41/03
26460	- CHANNEL LIGHT 13		FI G 4s	15	4	SG on pile.	
					*	*	41/03
27470	- LIGHT 9		FI G 6s	18	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*	*		41/03
28165	- Channel Daybeacon 47						Remove from list.
							* 41/03

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28280	- LIGHT 18		FI R 4s	15	3	TR on pile.	Light equipment removed when endangered by ice. Ra ref.
						*	41/03
28715	- SOUTH FERRY TERMINAL LIGHT 7	35 11 30 N 75 46 50 W	FI G 4s	15	4	SG on pile.	Ra ref.
						*	41/03
30990	- LIGHT 6		FI R 4s	16	2	TR on pile.	
						*	41/03
*31393	- Entrance Warning Daybeacon A					NW on pile worded DANGER SUBMERGED ROCKS.	
							41/03
32770	- LIGHT 7		FI G 4s	15	4	SG on pile.	
						*	41/03
33605	- LIGHT 1		FI G 4s	16	4	SG on pile.	
						*	41/03
*37047	- Entrance Warning Daybeacon A					NW on pile worded DANGER SUBMERGED ROCKS.	
							41/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>TAMPA BAY (Chart 11416)</b>							
<b>Tampa Bay</b>							
<b>Cut G Channel</b>							
23655	Cut G Preferred Channel Lighted Buoy G	27 47 04 N 82 31 23 W	FI (2+1) G 6s		3	Green and red bands.	
		*					41/03
<b>Fort George River</b>							
38275	- Daybeacon 2	30 26 47 N 81 26 42 W				TR on pile.	
		*					41/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
730	Mobil-GC-18A RACON						Remove from list.
							* 41/03

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*3243	- Lighted Buoy WR13A		<b>Q G</b>		3		41/03
4075 31570	- NAVY RANGE FRONT LIGHT	30 20 04 N 87 18 59 W	<b>FI G 2.5s</b> <b>FI G 2.5s</b>	34 36		KRW on skeleton tower on piles.	Visible all around, higher intensity on range line.  * * 41/03
<b>BARATARIA BAY AND APPROACHES (Chart 11358)</b>							
15250	QUATRE BAYOU PASS ENTRANCE LIGHT	29 18 38 N 89 51 21 W	<b>FI W 6s</b>	17	6	NG on dolphin.	Red sector visible from 340° to 070°.  * * 41/03
23830	LOWER RED LIGHT BEND INBOUND RANGE REAR LIGHT 70 yards, 276.8° from front light.		<b>Iso G 6s</b>	29		KRW on skeleton tower on piles.	Visible each side of rangeline.  * * 41/03
23835	LOWER RED LIGHT BEND OUTBOUND RANGE FRONT LIGHT	29 41 58 N 94 59 51 W	<b>Q R</b>	19		KRW on skeleton tower on piles.	Visible all around; higher intensity on rangeline.  * * 41/03
23837	LOWER RED LIGHT BEND OUTBOUND RANGE FRONT PASSING LIGHT						<i>Remove from list.</i>  * 41/03
23840	LOWER RED LIGHT BEND OUTBOUND RANGE REAR LIGHT 174 yards, 096.8° from front light.		<b>Iso R 6s</b>	29		KRW on skeleton tower on piles.	Visible all around; higher intensity on rangeline.  * * * 41/03
28100	- RANGE FRONT LIGHT	26 33 29 N 97 25 32 W	<b>Q R</b>	26		KRW on tower on piles.	Visible 2° each side of rangeline.  * 41/03
28360 40750	- RANGE A FRONT LIGHT	26 01 51 N 97 13 32 W	<b>Q W</b> <b>Q W</b>	33	6	KRW-I on skeleton tower.	Visible all around; higher intensity on range line.  * * 41/03
31570 4075	- NAVY RANGE FRONT LIGHT	30 20 04 N 87 18 59 W	<b>FI G 2.5s</b> <b>FI G 2.5s</b>	34 36		KRW on skeleton tower on piles.	Visible all around; higher intensity on rangeline.  * * 41/03
40750 28360	- RANGE A FRONT LIGHT	26 01 51 N 97 13 32 W	<b>Q W</b> <b>Q W</b>	33	6	KRW-I on skeleton tower.	Visible all around; higher intensity on range line.  * * 41/03

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
575 8650	<i>Rogue River Approach Lighted Whistle Buoy R</i>	42 23 38 N 124 28 35 W	<b>Mo (A) W</b>		6	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.  * 41/03
715 15170	<i>Willapa Bay Approach Lighted Whistle Buoy W</i>	46 44 00 N 124 11 00 W	<b>Mo (A) W</b>		6	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.  * 41/03
2871	- <i>Lighted Mooring Buoy</i>	33 44 54 N 118 10 09 W	<b>FI W 2s</b>			White with blue band.	Private aid.  * 41/03
3296	- <i>Lighted Mooring Buoy B</i>	33 42 40 N 118 16 13 W	<b>FI W 4s</b>			White spherical buoy with blue band.	Private aid.  41/03
5745	- Daybeacon 16  *	  *				Red nun.	41/03
<b>CAPE SEBASTIAN TO HUMBUG MOUNTAIN (Chart 18601)</b>							
<b>Rogue River</b>							
8650 575	- <i>Approach Lighted Whistle Buoy R</i>	42 23 38 N 124 28 35 W	<b>Mo (A) W</b>		6	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.  * 41/03
15170 715	- <i>Approach Lighted Whistle Buoy W</i>	46 44 00 N 124 11 00 W	<b>Mo (A) W</b>		6	Red and white stripes.	No topmark will be shown on this aid as required by IALA standards due to weather.  * 41/03
15790	- NORTH CHANNEL RANGE F REAR LIGHT 370 yards, 273.9° from front light.		<b>Iso W 6s</b>	45		KRB on pile structure.	Visible 5.5° each side of rangeline.  * 41/03
*28675.1	WOKAPU PENINSULA WECB LIGHT F	21 27 55 N 157 45 03 W	<b>FI Y 4s</b>	27		Yellow steel tripod.	Private aid.  41/03

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.